




FILTER ASSEMBLY- 600 D, DX




Step 1
Turn Power Off and unplug receptacle.
Lay unit upside down.




Step 2
With a #2 Philips screw driver, remove the four screws from the bottom of the unit.




Step 3
Gently grasp wheels.
Remove base by gently pulling on the wheels.




Step 4
Remove **only one** of the white, felt, donut-shaped gaskets from the inside of the purifier body.




Step 5
Insert the carbon filter (either a Model 600 D Carbon or a Model 600 DX Carbon) into the unit.




Step 6
Replace the gasket that had been removed in **STEP 4**.



Step 7
Place lid back to its proper position by aligning the arrow with the rear seam.



Step 8
Replace the four screws



Step 9
Turn the unit back onto its wheels. It is now ready for immediate use.



Model 600 Series

Operation and Maintenance Manual

AllerAir Industries Inc. 600 Series

Congratulations, you are moments away from fresher, cleaner indoor air. Your new **AllerAir** unit will combat many of the chemicals, gases, odors and particles responsible for poor indoor air quality, and in turn, health concerns such as allergies, asthma, sick building syndrome and multiple chemical sensitivity. As with any air cleaner, proper maintenance of your unit is a vital part of keeping it operating at peak efficiency.

WARNING !

Before removing the top or bottom of the unit for any reason, always unplug the cord from the power supply.

Operation:

Most 600 units are shipped fully assembled and ready for use with the exception of the D & DX models which ship with their large carbon filters in a separate box. This is done to safeguard your unit during shipping. To insert the filter, refer to the **Filter Assembly-600 D, DX** diagram.

Please plug units into a 120V-15amp outlet. For best results, situate your unit close to your sitting, sleeping or work area. The units equipped with a variable speed control -Turn knob to the right to adjust to your satisfaction-

Note: Please save your packaging. Original packaging will be required for all

Maintenance:

600 Series

HEPA Filter (Model 600 HEPA 2" or HEPA 3")

- Change the HEPA filter every 3 - 5 years or after a noticeable decrease in air quality.


Pre-Filter (Model 600 Prefilter)

- Change or vacuum the pre-filter every 2 - 4 months depending on the dust level in the area of use.

Carbon Filter (Model 600 Carbon Filter)

- Change the carbon filter after 2 years or after a noticeable decrease in air quality.


REPLACING FILTER ASSEMBLY- 600 Series



Step 1


Turn Power Off and unplug receptacle.

Lay unit upside down.




Step 2

With a #2 Philips screw driver, remove the four screws from the bottom of the unit.




Step 3

Gently grasp wheels.



Step 4


Remove base by gently pulling on the wheels.



Step 5

First remove the **HEPA filter** by placing thumbs on the inner side of the filter.


Then pull up gently until totally out.



Step 6


Then remove the **Carbon filter** by placing thumbs on the inner side of the filter.

Then pull up gently until totally out.




Step 7

Replace filters with new ones then reassemble by inserting the Carbon filter first then the HEPA filter.



Step 8

Place lid back to its proper position by aligning the arrow with the rear seam.



Step 9

With a screw driver, place 4 screws back into their positions. Gently return the unit into upright position.